



Expanded graphite gasket sheet

TEMAGRAPH TG

for high temperature and pressure parameters

Description:

Temagraph TG is high quality graphite sealing sheet reinforced with an expanded, free-dimensional, stainless steel insert. The unique geometry of the expanded metal insert combined with the excellent sealing properties of the expanded graphite foils, provide the sheet with excellent thermal and mechanical loading capabilities. Temagraph TG is especially suitable for petrochemical, oil, chemical and heating plant industry application.


Technical data:

Marking acc. to	DIN 28 091-4	GR-10-O-1 MK-Cr
Thickness (mm)		1,0 1,5 2,0 3,0
Max. temperature* (°C)		from -200 to +550
Max pressure* (bar)		200
Density (g/cm ³)		1,0-1,35
Ash content (%)	DIN 51 903	< 2,0
Chloride content (ppm)		< 50
Fluoride content (ppm)		< 50
Residual stress (N/mm ²)	Acc.to BS	37
Compressibility (%)	ASTM F 36A – 66	40
Recovery (%)	ASTM F 36A – 66	15
Sheet size		1500 x 1500 (1000 x 1000)*


*max. values can not be used simultaneously

** size on request

Printing / colour: violet



PT diagram



1-suitable subject to chemical compactability

2-suitable extended area, technical advice is recommended

3-for this area technical consultation is mandatory

Temac a.s. 28913 Zvěřinec Czech Republic	www.temac.cz	Page 1of 1	Approved: 5.4.2017 Valid since: 6.4.2017
--	--	------------	---

The given data is intended for information only. The manufacturer holds no responsibility for failures arising from bad application of the product. Interference with this document are prohibited.